



**UNIVERSITI PUTRA MALAYSIA**

**INFLUENCE OF A COMMERCIAL FUEL ADDITIVE ON  
COMBUSTION CHARACTERISTICS**

**MD ISA BIN ALI**

**FK 2001 38**

**INFLUENCE OF A COMMERCIAL FUEL ADDITIVE ON COMBUSTION  
CHARACTERISTICS**

**By**

**MD ISA BIN ALI**

**Thesis Submitted in Fulfilment of the Requirement for the  
Degree of Master of Science in the Faculty of Engineering  
Universiti Putra Malaysia**

**July 2001**



*To my wife and children, for  
their patience and support during  
the long preparation of this thesis.*

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment  
of the requirement for the degree of Master of Science

**INFLUENCE OF A COMMERCIAL FUEL ADDITIVE ON COMBUSTION  
CHARACTERISTICS**

**By**

**MD ISA BIN ALI**

**July 2001**

**Chairman: Associate Professor Md. Abul Hossain Mollah, Ph.D.**

**Faculty: Engineering**

The worse quality fuels in over 30 years have contributed to excessive emissions, poor performance and many others. Today, there exists a variety of fuel additives to perform under severe conditions to improve the fuel's combustion characteristics. However, the effectiveness and mode of operation of such additives are not completely understood.

This study discussed the experimental findings using a Combustion Laboratory Unit. Experiments were performed to determine the effects of a particular fuel additive on combustion characteristics which includes emissions, efficiency, heat release and the fuel consumption rate. Fuels (gasoline) with and without the additive were fired successively in the unit. MARVEL, a commercial fuel additive was used for the analysis. The concentration of the additive in the basic fuel were within 0.2% to 1.6% by volume.

It was found that, with the presence of the fuel additive, it decreased the carbon dioxide emission by 2%, maintained the carbon monoxide level less than 4% and the heat release increased by 5%. The additive was also found to increase the combustion efficiency by 8%, and decreased the fuel consumption rate by 5%.

From the above findings, the use of the additive to modify certain combustion characteristics of fuel can improve the basic fuel quality and performance. As this additive has been developed primarily for gasoline fuels, many such additives can also be employed in other type of fuel.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

**PENGARUH SEJENIS BAHAN TAMBAH KOMERSIAL BAHANAPI  
KE ATAS CIRI-CIRI PEMBAKARAN**

**Oleh**

**MD ISA BIN ALI**

**Julai 2001**

**Pengerusi: Profesor Madya Md. Abul Hossain Mollah, Ph.D.**

**Fakulti: Kejuruteraan**

Kualiti bahanapi yang kurang memuaskan disepanjang 30 tahun yang lampau, telah mengakibatkan beberapa masalah seperti pencemaran, prestasi yang kurang baik serta pelbagai lagi. Pada hari ini, telah wujud pelbagai jenis bahan tambah bahanapi dengan sifat-sifat yang tertentu untuk memperbaiki ciri-ciri pembakaran bahanapi tersebut. Walaubagaimanapun, keberkesanan dan kaedah operasi bahan tambah-bahan tambah itu masih belum diketahui sepenuhnya.

Kajian ilmiah ini membincangkan hasil ujikaji dengan menggunakan sebuah Radas Analisa Pembakaran.. Ujikaji-ujikaji telah dijalankan untuk mengkaji pengaruh bahan tambah ke atas ciri-ciri pembakaran termasuk komposisi gas ekzos, haba terhasil, kecekapan pembakaran keseluruhan dan akhir sekali kadar penggunaan bahanapi. Bahanapi (gasoline) berserta bahan tambah dan bahanapi tanpa bahan tambah telah dibakar di dalam radas tersebut. Sejenis bahan tambah komersial, MARVEL, telah digunakan dalam kajian ini. Peratusan bahan tambah yang

dicampurkan ke dalam bahanapi adalah diantara 0.2% hingga 1.6% pada nisbah isipadu.

Adalah didapati bahawa, dengan kehadiran bahan tambah tersebut, pengeluaran karbon dioksida berkurang sebanyak 2%, mengekalkan paras karbon monoksida di bawah 4% dan kadar haba dihasilkan meningkat sebanyak 5%. Bahan tambah ini juga didapati dapat meningkatkan kecekapan pembakaran sebanyak 8% serta mengurangkan kadar penggunaan bahanapi sehingga 5%.

Daripada keputusan di atas, didapati, dengan penggunaan bahan tambah untuk mengubah ciri-ciri pembakaran bahanapi, ia juga boleh memperbaiki kualiti dan prestasi bahanapi tersebut. Bahan tambah yang dibincangkan ini pada asasnya adalah untuk bahanapi gasoline. Terdapat banyak lagi bahan tambah lain yang juga boleh digunakan untuk jenis-jenis bahanapi lain.

## **ACKNOWLEDGEMENTS**

First of all, I would like to express my deepest and warmest thanks and appreciation to my chairman, Associate Professor Dr. Md. Abul Hossain Mollah and members of the supervisory committee, Dr. Megat Mohamad Hamdan B. Megat Ahmad and Ir. Fuad Abas, for the guidance and advice through out the duration of this study.

Thanks also extended to Ir. Khor Bok Chim, The Principal, Polytechnic of Port Dickson, Negeri Sembilan, and Mohd. Ghaus B. Ab. Kadir, Head of Mechanical Engineering Department, Polytechnic of Port Dickson, for their permission to use their laboratory facilities to conduct this study.

I also want to acknowledge my debt to those of my colleagues, Mohd Asri Sarbun and Azmi Udi at the Mechanical Engineering Department, Polytechnic of Port Dickson, who have helped me to develop and set up the laboratory facilities. I also wish to express my gratitude to Isa Kasim, a senior lecturer from the same department, who worked well beyond the call of duty to assist the laboratory studies.

In addition, my greatest thanks are given to my family who provides me the encouragement, sympathy, understanding and tolerance which are so necessary during the many hours of commitment required for conducting the study and for the writing of the thesis.





Without the anticipation of their help and availability, I could not have contemplated embarking on this project.

I certify that an Examination Committee met on 13<sup>th</sup> July 2001 to conduct the final examination of Md Isa Bin Ali on his Master of Science thesis entitled "Influence of a Commercial Fuel Additive On Combustion Characteristics" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree ) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

**MD. YUSOF ISMAIL, Ir., Ph.D.**

Associate Professor,  
Department of Mechanical and Manufacturing,  
Faculty of Engineering,  
Universiti Putra Malaysia.  
(Chairman)

**MD. ABUL HOSSAIN MOLLAH, Ph.D.**


Associate Professor,  
Department of Mechanical and Manufacturing,  
Faculty of Engineering,  
Universiti Putra Malaysia.  
(Member)

**MEGAT MOHAMAD HAMDAN B. MEGAT AHMAD, Ph.D.**

Department of Mechanical and Manufacturing,  
Faculty of Engineering,  
Universiti Putra Malaysia.  
(Member)

**FUAD ABAS, Ir.**

Department of Mechanical and Manufacturing,  
Faculty of Engineering,  
Universiti Putra Malaysia.  
(Member)

  
**MOHD. GHAZALI MOHAYIDIN, Ph.D.**  
Professor,  
Deputy Dean of Graduate School,  
Universiti Putra Malaysia.

Date: 17 AUG 2001

This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfilment of the requirement for the degree of Master of Science.



---

**AINI IDERIS, Ph.D.**  
Professor,  
Dean of Graduate School,  
Universiti Putra Malaysia

Date : 13 SEP 2001

## DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.



---

MD. ISA BIN ALI

Date : 17 AUG 2001

## TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	v
ACKNOWLEDGEMENTS	vii
APPROVAL SHEETS	ix
DECLARATION FORM	xi
LIST OF TABLES	xiv
LIST OF FIGURES	xvii
LIST OF ABBREVIATIONS	xix

### CHAPTER

1	INTRODUCTION	1
1.1	Problem Statement	2
1.2	Scope of Study	2
1.3	Objectives	3
1.4	Benefit of Study	3
2	LITERATURE REVIEW	5
2.1	Fuel Additives	14
2.2	Combustible Fuel	18
2.2.1	Desirable Characteristics of a Fuel	20
2.3	Combustion Application	20
2.4	Combustion Equation	21
2.5	Combustion Chemistry	22
2.6	Combustion Calculation	24
2.7	Factors Affecting Combustion Performance	27
2.7.1	Burner or Nozzle Design	27
2.7.2	Fire Chamber	27
2.7.3	Waste Heat Energy Losses in Stack Gases	28
2.7.4	Effect of Air/fuel Ratio	28
2.7.5	Poorly Maintained Due to Incomplete Combustion	28
2.7.6	Effect of Combustion Gas Exit Temperature	29
2.7.7	Effect of Fuel Properties	29
2.8	Emission and Pollution	30
2.9	Emission Control and Combustion Aids	31
2.10	Selection of Additive and Fuel	33
3	MATERIAL AND METHODS	35
3.1	Experimental Apparatus	35



3.1.1	Combustion Laboratory Unit	35
3.1.2	Single Cylinder Engine Test Bed	45
3.2	Experimental Set-up	48
3.2.1	Combustion Laboratory Unit	48
3.2.2	Fuel Consumption Test	50
4.	RESULTS AND DISCUSSIONS	52
4.1	Effect of Fuel Additive on the Flue Gas Composition	52
4.1.1	Effect of Fuel Additive on the CO <sub>2</sub> emission	52
4.1.2	Effect of Fuel Additive on the CO emission	57
4.1.3	Effect of Fuel Additive on the O <sub>2</sub> emission	60
4.2	Effect of Fuel Additive on Combustion Efficiency	63
4.3	Effect of Fuel Additive on Heat Release	67
4.4	Effect of Fuel Additive on Fuel Consumption	69
5	CONCLUSIONS	73
	REFERENCES	75
	APPENDICES	79
	BIODATA OF THE AUTHOR	140

## LIST OF TABLES

<b>Table</b>	<b>Page</b>
2.1 Effect of detergents and anti-icing additive	6
2.2 Effect of oxidation, corrosion and wear inhibitor	7
2.3 Effect of corrosion and rust inhibitor	8
2.4 Effect of antiwear additive	10
2.5 Result of smoke suppressant test	11
2.6 Spread of air/fuel ratio	12
2.7 Effect of a catalytic agent	13
2.8 Gasoline fuel additives	16
2.9 Diesel fuel additives	17
2.10 Typical composition and energy content of liquid fuel	18
2.11 Properties of automotive fuels	19
2.12 Some application of combustion	20
2.13 Malaysian emission standard for petrol engine in use	32
3.1 Experimental programme for Combustion Lab. Unit	50
3.2 Experimental programme for fuel consumption test	51
E1 Fuel without additive	93
E2 Fuel with 0.2% additive	94
E3 Fuel with 0.4% additive	95
E4 Fuel with 0.6% additive	96
E5 Fuel with 0.8% additive	97

E6	Fuel with 1.0% additive	98
E7	Fuel with 1.2% additive	99
E8	Fuel with 1.4% additive	100
E7	Fuel with 1.6% additive	101
F1	Combustion products for fuel without additive	103
F2	Combustion products for fuel with 0.2% additive	104
F3	Combustion products for fuel with 0.4% additive	105
F4	Combustion products for fuel with 0.6% additive	106
F5	Combustion products for fuel with 0.8% additive	107
F6	Combustion products for fuel with 1.0% additive	108
F7	Combustion products for fuel with 1.2% additive	109
F8	Combustion products for fuel with 1.4% additive	110
F9	Combustion products for fuel with 1.6% additive	111
G1	Gas absorption analysis for fuel without additive	113
G2	Gas absorption analysis for fuel with 0.2% additive	114
G3	Gas absorption analysis for fuel with 0.4% additive	115
G4	Gas absorption analysis for fuel with 0.6% additive	116
G5	Gas absorption analysis for fuel with 0.8% additive	117
G6	Gas absorption analysis for fuel with 1.0% additive	118
G7	Gas absorption analysis for fuel with 1.2% additive	119
G8	Gas absorption analysis for fuel with 1.4% additive	120
G9	Gas absorption analysis for fuel with 1.6% additive	121
H1	Heat distribution analysis for fuel without additive	123



H2	Heat distribution analysis for fuel with 0.2% additive	124
H3	Heat distribution analysis for fuel with 0.4% additive	125
H4	Heat distribution analysis for fuel with 0.6% additive	126
H5	Heat distribution analysis for fuel with 0.8% additive	127
H6	Heat distribution analysis for fuel with 1.0% additive	128
H7	Heat distribution analysis for fuel with 1.2% additive	129
H8	Heat distribution analysis for fuel with 1.4% additive	130
H9	Heat distribution analysis for fuel with 1.6% additive	131
I1	Fuel consumption test for fuel without additive	133
I2	Fuel consumption test for fuel with 0.2% additive	133
I3	Fuel consumption test for fuel with 0.4% additive	134
I4	Fuel consumption test for fuel with 0.6% additive	134
I5	Fuel consumption test for fuel with 0.8% additive	135
I6	Fuel consumption test for fuel with 1.0% additive	135
I7	Fuel consumption test for fuel with 1.2% additive	136
I8	Fuel consumption test for fuel with 1.4% additive	136
I9	Fuel consumption test for fuel with 1.6% additive	137
J1	Economic analysis of fuel additive usage for the engine at 2500 rpm	139



## LIST OF FIGURES

Figure	Page
3.1 Combustion Laboratory Unit (front view)	37
3.2 Combustion Laboratory Unit (side view)	38
3.3 Combustion Laboratory Unit (side view)	39
3.4 Orsat Gas Analyser	42
3.5 Single Cylinder Engine Test Bed	46
4.1 Effect of fuel additive on CO <sub>2</sub> emission	54
4.2 Effect of fuel additive on CO <sub>2</sub> emission at a particular air/fuel ratio	56
4.3 Effect of fuel additive on CO emission	58
4.4 Effect of fuel additive on CO emission at a particular air/fuel ratio	59
4.5 Effect of fuel additive on O <sub>2</sub> emission	61
4.6 Effect of fuel additive on O <sub>2</sub> emission at a particular air/fuel ratio	62
4.7 Effect of fuel additive on combustion efficiency	65
4.8 Effect of fuel additive on combustion efficiency at a particular air/fuel ratio	66
4.9 Effect of fuel additive on heat distribution at 15.0 A/F	68
4.10 Effect of fuel additive on fuel consumption	70
4.11 Effect of fuel additive on fuel consumption at a particular engine speed	71
A1 Combustion Laboratory Unit (schematic diagram)	80
A2 Combustion Laboratory Unit (schematic diagram - front view)	81
A3 Combustion Laboratory Unit (schematic diagram - side view)	82



B1	Orsat flue gas analyzer (schematic diagram)	84
D1	Fuel consumption test	88

## LIST OF ABBREVIATIONS

$Q_f$	Heat input from fuel
$Q_c$	Heat loss due to cooling water
$Q_e$	Heat loss to exhaust gases
$Q_s$	Heat loss to the unit surfaces
$Q_L$	Unaccounted heat loss
$\eta_c$	Combustion efficiency
$m_f$	Fuel mass flow rate
$m_w$	Water mass flow rate
$m_g$	Mass of dry fuel gas per mass of fuel fired
LHV	Fuel lower heating value
$c_{pw}$	Constant pressure specific heat for water
$c_{pg}$	Mean constant pressure specific heat of dry flue gases
$T_{w1}$	Water inlet temperature
$T_{w2}$	Water outlet temperature
$T_e$	Exhaust outlet temperature
$T_a$	Air supply temperature
HC	Hydrocarbon
ppm	Part per million
V	Volume of pipette
$\rho_f$	Density of the fuel
t	Time taken to consume the fuel

## **CHAPTER 1**

### **INTRODUCTION**

Combustion is defined as a chemical reaction in which a fuel combines with oxygen liberating large quantities of heat and incidentally light.

The mechanism of combustion, particularly that of complex hydrocarbons, is complicated and is not fully understood. Combustion does not proceed directly from the air-fuel mixture to the final products. Rather, partial oxidation of the fuel occurs at first, and intermediate products are formed. Ultimately, if conditions are right, combustion becomes complete.

Attempts to improve basic petroleum product by non-hydrocarbon additive treatment have existed as long as the petroleum industry itself. Nowadays, certain chemical materials are marketed as additives for some liquid fuels, either to improve their combustion characteristics or to alleviate low temperature corrosion problems due to the fuel's sulphur content. Some common fuel additives are such as oxidation inhibitors, corrosion inhibitors, anti-icing additives, anti-knock compound and dyes.

A host of properties exhibited by fuel (gasolines) results from the use of additives. For example, oxidation inhibitors make gasolines less susceptible to oxidation; this allows the gasoline to be stored for many weeks without excessive gum.

### **1.1 Problem Statement**

The use of additives to modify certain physical or chemical characteristics of fuel have been mentioned in most literature. The research activity in most of the literature emphasize the major contribution of a given type of fuel additive to increase the efficiency which centered on the effectiveness of the additive to provide variety of improvements such as knocking, excessive corrosion, and many others. But, how does the additives affects the combustion characteristics such as the combustion efficiency, emissions, and the heat release are not clearly described.

### **1.2 Scope of Study**

A study of the effect of the additives is carried out by using a combustion laboratory unit. Fuels with and without additive are fired succesively in the unit and analyses of performance is made.

The majority of the experiments in this study falls into the combustion with the fuel additive and its influence to the combustion characteristics which includes emissions, combustion efficiency and heat release in the unit.

The effect of the additive on the fuel consumption are also included. A single cylinder engine test bed is used for this purpose.

Under the heading of combustion characteristics, other than those dictated above, are included flame speed, reaction rates and flame propagation. However, since the study of the very complicated phases of combustion is beyond the scope of this study, the reader is referred to the references.

### **1.3 Objectives**

The objectives of this study is to study the effect of the fuel additive on :-

- i. Flue gas composition.
- ii. Combustion efficiency.
- iii. Heat release (distribution) in the combustion laboratory unit.
- iv. Fuel consumption of an engine.

### **1.4 Benefit of Study**

- i. The findings can be used as a valuable information to the fuel users so that they can plan the used of their fuel safely and economically.
- ii. The findings might provide many new business opportunities and a challenge to the additives manufacturers about the need for more effective fuel additive to increase efficiency, while at the same time decreasing the emissions of pollutant.

- iii. The findings can be used by any interest organizations especially Department of Environment (DOE), Road and Transport Department (RTD) to plan their environment friendly programmes.



## **CHAPTER 2**

### **LITERATURE REVIEW**

Fuels additive are designed to help solve poor quality fuel problems - burned valves, excessive emissions, hesitation, knocking and so on – and vehicle maintainers have caught on their importance.

Today, there exist a variety of combustion or fuel additives to perform under extremely severe conditions. It is found that the additives have been a solution to many problems and substantial reduction in emissions, wear, maintenance and down time.

G.E Gaston (1982) describes a gasoline motor fuel having improved anti-icing, detergency, antirust and ignition control characteristics. It is obtained by incorporating in the fuel a small amount of a combination of a polyoxypropylene monooleate and N-tallow trimethylenediamine naphthenate.

To illustrate the nature of the improvement obtained, presented in Table 2.1, are the results obtained with engine tests made upon a base gasoline motor fuel (A) and the same base gasoline motor fuel containing an additive (B).